



CFC 90

for Cold Formed



CFC 90

For 90° corners with cold formed sheet piles
(as interlocks vary, specific swivel range is not stated, but some swivel should be expected)

Installation

1. Please review the proper interlocking examples that are listed.
2. Thread the connector into the interlock while the sheet pile is out of the ground.
3. Adjust the connector to the appropriate position.
4. Tack or spot-weld the connector in place. Typically, a ~250mm (~10") weld, attaching the connector to the sheet pile to the top is sufficient.
5. Drive/extract the sheet pile (with the connector attached) as you would normally.

Properties

Steel grade:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Weight:	~ 12.0 lb/ft



CFC 90

90° Eckverbindung
Für Leichtprofile

Einsatzgebiet

Erstellen von 90°-Eckverbindungen



Eigenschaften

Stahlgüten:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Gewicht:	~ 17,9 kg/m



CFC 90

Unión angular de 90°
Para perfiles ligeros

Ámbito de aplicaciones

Formación de uniones angulares de 90°

Propiedades

Calidades de acero:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Peso:	~ 17,9 kg/m



CFC 90

Raccords d'angles à 90°
Pour profilés légers

Domaines d'emploi

Fabrication de raccords d'angles à 90°

Caractéristiques

Nuances d'acier:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Poids:	~ 17,9 kg/m



CFC 90

Connessione per angolo a 90°
Per profili leggeri

Campo di applicazione

Realizzazione di angoli a 90°

Caratteristiche

Qualità dell'acciaio:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Peso:	~ 17,9 kg/m

