



PBS-M / PBS-F

For combined walls (Peiner-type beams) with PZ/PZC (ball & socket) sheet piles

Installation

1. Install the Peiner Beams first.
2. Lay the sheet piling horizontally and thread the connector into the interlock of the sheet piling, adjusting the connector to the appropriate position (please review the proper interlocking examples, as shown to the right). This can be done at the mill, at a distributor's yard, or on the job site (go here: www.PilePro.com/thread).
3. Tack or spot-weld the connector in place. Typically, a ~250mm (~10") weld, attaching the connector to the sheet pile to the top is sufficient.
4. Grasp the sheet pile (with connectors already attached) and thread between the already installed Peiner type beams.
5. Lower/drive the sheet piling to the level of the Peiner type beam.

Properties

Steel grade:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Weight PBS-M:	~ 9 lb / ft
Weight PBS-F:	~ 10.66 lb / ft



PBS-M / PBS-F

Kombiwandprofile

Für PZ und PZC (Ball and Socket)

Einsatzgebiet

Erstellen von Kombiwänden mit Keulenträgern und PZ/PZC-Profilen



Eigenschaften

Stahlgüten:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Gewicht PBS-M:	~13,4 kg/m
Gewicht PBS-F:	~15,9 kg/m



PBS-M / PBS-F

Perfiles de pantalla combinada

Para PZ y PZC (Ball and Socket)

Ámbito de aplicaciones

Formación de pantallas combinadas con portamazas y perfiles PZ/PZC

Propiedades

Calidades de acero:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Peso PBS-M:	~13,4 kg/m
Peso PBS-F:	~15,9 kg/m



PBS-M / PBS-F

Raccord pour rideaux mixtes

Pour PZ et PZC (Ball + Socket)

Domaines d'emploi

Rideaux mixtes avec des poutres de soutien et des profilés PZ/PZC

Caractéristiques

Nuances d'acier:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Poids PBS-M:	~13,4 kg/m
Poids PBS-F:	~15,9 kg/m



PBS-M / PBS-F

Profilo parete combinata

Per PZ e PZC (maschio e femmina)

Campo di applicazione


Realizzazione di pareti combinate con travi a doppia T e profili PZ/PZC

Caratteristiche

Qualità dell'acciaio:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Peso PBS-M:	~13,4 kg/m
Peso PBS-F:	~15,9 kg/m



PBS-M



PBS-F

